

# Arch POS Receipt Printer

## Technical Specifications

<b>Printing</b>	Print Method Resolution Print Speed Printing Width	Direct Thermal Line Printing Standard 203dpi (8dots/mm), Emulated 180dpi (7dots/mm) Max.260mm/s 72mm
<b>Interface</b>	Standard Optional	USB+Serial+Ethernet Bluetooth or Wi-Fi
<b>Page Mode</b>		Support
<b>Memory</b>	RAM Flash	32Mb 64Mb
<b>Fonts</b>	Chinese Alphanumeric User-defined Codepage	GBK 24x24dots ASCII 9x 17, 12x24dots YES 48
<b>Barcode</b>	1D  2D	UPC-A, UPC-E, EAN8, EAN13, CODE39, ITF, CODEBAR, CODE128, CODE93 PDF417, QR code
<b>Graphics</b>		Support bitmap printing with different density and user defined bitmap printing. (Max size of each bitmap is 64K, the total size of bitmap is 256k)
<b>Detection</b>	Sensors	Paper out and paper near end sensors, cover open switch
<b>LED Indicator</b>	Power Paper Error	Blue LED Orange LED Red LED
<b>Reliability</b>	TPH life Cutter life	150km 2 million cuts
<b>Power Supply</b>	Input Output	AC 100V-240V DC 24V/2.5A
<b>Paper</b>	Paper Type Paper Width Paper Thickness Roll Paper Diameter Paper Load Paper Cut	Thermal Receipt Paper 58mm/80mm 0.056-0.1mm Max. OD $\phi$ 83mm Front or Top paper loading Partial cut or full cut
<b>Environment</b>	Operation Storage	0°C-45°C, 25%~85%RH -30°C-60°C, 5%-95%RH
<b>Physical Characteristics</b>	Dimension Weight	134.8(L)x132(W)x132(H)mm 1.37KG (Without paper roll)
<b>Options &amp; Accessories</b>		USB / Serial Cable, Paper Roll, Power Adapter, Power Cord, CD, Quick Start Guide
<b>Software</b>	Emulation Driver	ESC / POS Windows2000 / XP / Win7 / Win8 / Win 10 / POSReady / Linux / OPOS /
	SDK	WinCE, Win Mobile, Android, iOS

### CONTACT US

Tel: +27 21 556 2724  
Email: [webinfo@archretail.com](mailto:webinfo@archretail.com)  
Website: [www.archretail.com](http://www.archretail.com)

